



The specification of the "Sabre" is remarkably complete including as standard equipment, a powerful fresh air heating and demisting system, windscreen washers, electric clock and a cigar lighter—features usually costing extra.

Brief leading particulars are:-

POWER UNIT.—1.7 litre O.H.V. 4-cylinder engine developing 61 B.H.P. at 4,400 r.p.m. Automatic cooling by thermostat-controlled electric fan. All synchromesh, crash-proof four speed gearbox with floor gear change.

**BODY.**—All-fibreglass with full wrap-round windscreen, wind-up door windows, and front-hinged bonnet giving easy access to engine and front suspension.

FASCIA.—Complete range of instruments set in hooded nacelle with anti-glare finish.

CHASSIS.—Deep box section giving tremendous strength and torsional rigidity.

SUSPENSION.—Front: independent swinging arm. Rear: modified Watt linkage with combined coil spring and hydraulic damper units all round.

REAR AXLE.—Semi-floating. Spiral bevel differential with composite light alloy and steel tube casing. Final ratio 3.55 to 1.

STEERING.—By wood-rimmed steering wheel through silent bloc universal coupling to rack and pinion.

LIGHTING.—Lucas 12-volt equipment with powerful sealed beam headlamps.

WHEELS.—Pressed steel with chrome nave plates fitted with 155×15 sports tyres. Wire wheels optional extra.

DIMENSIONS.—Length, 13ft. 9in.
Track, 4ft. Width, 5ft. 1in. Wheelbase, 7ft. 6in.
Height, 4ft. 2in. Ground Clearance, 5in.

PERFORMANCE,—Up to 100 m.p.h. Petrol consumption up to 32 m.p.g.

BRAKES.—11in. disc brakes on front—wide 9in. diameter drums on rear.

PRICE.—Soft Top only, £1,128 10s. 7d., including Purchase Tax and Surcharge ex works.

## the all new

## RELIANT Sabre



V. reliant engineering co. (TAMWORTH) LTD., TWO GATES, Nr. TAMWORTH, STAFFS.